

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** SCHULLER

**Supplier's address:** Quality Manager, CARRETERA DEL PLA KM 1.5, 46117 BETERA BETERA VALENCIA, ES

**Model identifier:** 786577

## Type of light source:

|   |                                     |                                 |      |
|---|-------------------------------------|---------------------------------|------|
| Lighting technology used:                           | LED                                 | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | COLETTE LED CEILING LAMP 80, CHROME |                                 |      |
| Mains or non-mains:                                 | MLS                                 | Connected light source (CLS):   | No   |
| Colour-tuneable light source:                       | No                                  | Envelope:                       | -    |
| High luminance light source:                        | No                                  |                                 |      |
| Anti-glare shield:                                  | No                                  | Dimmable:                       | Yes  |

## Product parameters

| Parameter  | Value                  | Parameter  | Value                              |
|--|------------------------|--|------------------------------------|
| <b>General product parameters:</b>   |                        |  |                                    |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer  | 65                     | Energy efficiency class  | F                                  |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 5 850 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000                              |
| On-mode power ( $P_{on}$ ), expressed in W   | 65,0                   | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal   | 0,00                               |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal  | -                      | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 80                                 |
| Outer dimensions without separate con-   | Height                 | 16   | Spectral power distribution in the |
|  | Width                  | 1  |                                    |
|  | Depth                  | 1  |                                    |
|  |                        |  | See image in last page             |


|   |      |                                       |                                      |  |
|---|------|---------------------------------------|--------------------------------------|--|
| trol gear, lighting control parts and non-lighting control parts, if any (millimetre)                                   |      |                                       | range 250 nm to 800 nm, at full-load |  |
| Claim of equivalent power <sup>(a)</sup>  | Yes  | If yes, equivalent power (W)          | 200                                  |  |
|   |      | Chromaticity coordinates (x and y)    | 0,001<br>0,001                       |  |
| <b>Parameters for LED and OLED light sources:</b>   |      |                                       |                                      |  |
| R9 colour rendering index value   | 0    | Survival factor                       | 0,00                                 |  |
| the lumen maintenance factor  | 0,00 |                                       |                                      |  |
| <b>Parameters for LED and OLED mains light sources:</b>   |      |                                       |                                      |  |
| displacement factor (cos $\phi_1$ )   | 0,00 | Colour consistency in McAdam ellipses | 0                                    |  |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | _(b) | If yes then replacement claim (W)     | -                                    |  |
| Flicker metric (Pst LM)   | 0,0  | Stroboscopic effect metric (SVM)      | 0,0                                  |  |

(a) : not applicable;

(b) : not applicable;



Model placed on the Union market from 28/02/2019



**EPREL registration number:** 1035571

<https://eprel.ec.europa.eu/qr/1035571>

**Supplier:** SCHULLER S.L. (Importer)

**Website:**

**Customer care service:**

**Name:** Quality Manager

**Website:** [www.schuller.es](http://www.schuller.es)

**Email:** [ricardoschuller@schuller.es](mailto:ricardoschuller@schuller.es)

**Phone:** +34 961 60 10 51

**Address:**

CARRETERA DEL PLA KM 1.5

46117 BETERA

Spain