

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** LOOM Design

**Supplier's address:** Main Office, Lilleringvej 30, 8462 Aarhus Harlev, DK

**Model identifier:** 805-013

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	SMD		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes

## Product parameters

Parameter	Value	Parameter	Value
<b>General product parameters:</b>			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	24	Energy efficiency class	E
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	2 900 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 738
On-mode power ( $P_{on}$ ), expressed in W	24,0	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0,00
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer dimensions without separate control gear, lighting control	Height	450	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	450	
	Depth	3	
			See image in last page

parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,451 0,400
<b>Parameters for LED and OLED light sources:</b>			
R9 colour rendering index value	65	Survival factor	0,90
the lumen maintenance factor	0,96		

(a) : not applicable;

(b) : not applicable;

## Spectrum Test Report

Sample : Downlight  
Specification : LUCIA 450-C-26W-927  
Sample No. : RP-210398-8  
Manufacturer : V

Date : 2021-08-26 10:06:09  
Sam. Status :  
Instrument : HAAS-2000(EVERFINE)  
Test by : hanyu YI

### Test Condition

Temperature : 25.3Deg  
WL Range : 380nm-780nm  
Test Mode : Fast Test

RH : 65.0%  
IP : 52450 (80%)  
T : 94 ms  
Sensitivity : High

### Spectrum



### Colorimetric Parameters

Chromaticity Coordinate:  $x = 0.4515$   $y = 0.4003$  /  $u' = 0.2617$   $v' = 0.5221$  ( $duv = -3.15e-03$ )

CCT= 2738K Prcp WL: Ld=585.1nm Purity=55.7%

Peak WL: Lp=624nm FWHM: =135.9nm Ratio:R=26.7% G=70.0% B=3.3%

Render Index: Ra = 92.2

R1 =97 R2 =97 R3 =93 R4 =93 R5 =96 R6 =92 R7 =88

R8 =81 R9 =65 R10=95 R11=95 R12=81 R13=99 R14=97 R15=92

LEVEL:OUT WHITE:ANSI\_2700K

### Photometric & Radiometric Parameters


Flux = 3031.9 lm Eff. : 132.33 lm/W Fe = 10.849 W

### Electrical parameters

V = 32.74 V I = 0.6999 A P = 22.91 W PF = 1.000 F=0.00 Hz

E-LITE LIGHTING Co.,Ltd.

Model placed on the Union market from 08/02/2021



**EPREL registration number:** 1115364

<https://eprel.ec.europa.eu/qr/1115364>

**Supplier:** Lampefeber A/S (Importer)

**Website:** [www.lampefeber.com](http://www.lampefeber.com)

**Customer care service:**

**Name:** Main Office

**Website:**

**Email:** [mail@lampefeber.com](mailto:mail@lampefeber.com)

**Phone:** 86361722

**Address:**

Lilleringvej 30  
8462 Harlev  
Denmark