

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** LOOM Design

**Supplier's address:** Main Office, Lilleringvej 30, 8462 Harlev, DK

**Model identifier:** 805-006

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	SMD		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes

## Product parameters

Parameter	Value	Parameter	Value
<b>General product parameters:</b>			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	36	Energy efficiency class	E
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	4 700 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 751
On-mode power ( $P_{on}$ ), expressed in W	36,0	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0,00
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer dimensions without separate control gear, lighting control	Height	600	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	600	
	Depth	2	
			See image in last page

parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,451 0,401
<b>Parameters for LED and OLED light sources:</b>			
R9 colour rendering index value	66	Survival factor	0,90
the lumen maintenance factor	0,96		

(a) : not applicable;

(b) : not applicable;

## Spectrum Test Report

Sample : 2 Date : 2021-09-02 11:15:44  
Specification : LUCIA 600-C-46W-927 Sam. Status :  
Sample No. : RP-210486-4 Instrument : HAAS-2000(EVERFINE)  
Manufacturer : E-LITE LIGHTING CO,LTD Test by : hanyu YI

### Test Condition

Temperature : 25.3Deg RH : 65.0%  
WL Range : 380nm-780nm IP : 54386 (83%)  
Test Mode : Fast Test T : 54 ms  
Sensitivity : High

### Spectrum



### Colorimetric Parameters

Chromaticity Coordinate:  $x = 0.4515$   $y = 0.4030$  /  $u' = 0.2605$   $v' = 0.5232$  ( $duv = -2.10e-03$ )

CCT= 2760K Prcp WL:  $L_d = 584.6\text{nm}$  Purity=56.5%

Peak WL:  $L_p = 621\text{nm}$  FWHM: =140.0nm Ratio:R=26.4% G=70.4% B=3.2%

Render Index:  $R_a = 92.9$

R1 =96 R2 =98 R3 =94 R4 =93 R5 =96 R6 =94 R7 =89

R8 =82 R9 =65 R10=98 R11=95 R12=83 R13=98 R14=98 R15=92

LEVEL:OUT WHITE:ANSI\_2700K

### Photometric & Radiometric Parameters


Flux = 5525.9 lm Eff. : 115.99 lm/W Fe = 19.705 W

### Electrical parameters

V = 34.03 V I = 1.40 A P = 47.64 W PF = 1.000 F=0.00 Hz

E-LITE LIGHTING CO.LTD

Model placed on the Union market from 30/06/2022



**EPREL registration number:** 1254632

<https://eprel.ec.europa.eu/qr/1254632>

**Supplier:** Lampefeber A/S (Importer)

**Website:** [www.lampefeber.com](http://www.lampefeber.com)

**Customer care service:**

**Name:** Main Office

**Website:**

**Email:** [mail@lampefeber.com](mailto:mail@lampefeber.com)

**Phone:** 86361722

**Address:**

Lilleringvej 30  
8462 Harlev  
Denmark