

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LOOM Design

Supplier's address: Main Office, Lilleringvej 30, 8462 Aarhus Harlev, DK

Model identifier: 840-004

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	SMD		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	6	Energy efficiency class	G
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	373 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 982
On-mode power (P_{on}), expressed in W	6,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer dimensions without separate control gear, light-	Height	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width		
	Depth		

ing control parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,438 0,405	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	60	Survival factor	0,90	
the lumen maintenance factor	0,97			

(a) '-': not applicable;

(b) '-': not applicable;

Light Source Test Report



Color Parameters:

Chromaticity Coordinate: $x=0.4386$ $y=0.4053$ Chromaticity Coordinate: $u'=0.2511$ $v'=0.5221$ ($duv=2.49e-04$)

Tc=2982K Dominant WL:Ld=582.8nm Purity=53.3% Centroid WL:602.0nm

Ratio:R=25.9% G=71.3% B=2.7% Peak WL:Lp=620.0nm HWL:161.8nm

Render Index:Ra=92.6 CRI=89.7

R1 =93 R2 =97 R3 =99 R4 =91 R5 =92 R6 =96 R7 =91

R8 =82 R9 =60 R10=92 R11=92 R12=77 R13=94 R14=99 R15=89

Photo Parameters:

Flux: 292.01 lm Fe: 1.0180 W Efficacy:50.14 lm/W

Electrical Parameters:

Lamp : U=229.86V I=0.04828A P=5.823W PF=0.5247

Instrument Status:

Scan Range:380.0nm-800.0nm Interval:5.0nm[0]

REF=3876 (R=4)

%=-0.053%


Ip=2190 (G=3, D=51)

PMT: 19.9 centigrade [20.2]

Product Type:
Number:
Temperature:25.3 deg
Test Operator:J01
Software:V3.00.137

Manufacturer:
Test Department:
Humidity:65.0%
Test Date:2021-11-23 08:46:03
Instrument:PMS-50SSA_V1 (SN:1004060)

Model placed on the Union market from 01/03/2023



EPREL registration number: 1517757

<https://eprel.ec.europa.eu/qr/1517757>

Supplier: Lampefeber A/S (Importer)

Website: www.lampefeber.com

Customer care service:

Name: Main Office

Website: www.loom-design.com

Email: mail@lampefeber.com

Phone: +4586361722

Address:

Lilleringvej 30
8462 Harlev
Denmark