

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: GLOBO Handels GmbH

Supplier's address: GLOBO Handels GmbH, Gewerbestraße 3, 9184 St. Peter, AT

Model identifier: 78408-12

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	connection by couple connector		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	12	Energy efficiency class	E
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 600 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power (P_{on}), expressed in W	11,5	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	82
Outer dimensions without separate control gear, lighting control	Height	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width		
	Depth		

parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,440 0,403	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	10	Survival factor	0,90	
the lumen maintenance factor	0,95			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ_1)	0,92	Colour consistency in McAdam ellipses	2	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,1	

(a) '-': not applicable;

(b) '-': not applicable;

Lightsource Test Report

Product Information

Product Type: 78408-12-ld

Product Number: 171

CIE Colorimetric Parameters

Chromaticity coordinates: $x=0.4331$ $y=0.3974$ $u(u')=0.2510$ $v=0.3454$ $v'=0.5181$ CCT: $T_c=3010K$ ($duv=-0.00217$)Color Ratio: $R=0.232$ $G=0.739$ $B=0.029$

Peak Wavelength: 603.2nm

Half Bandwidth: 123.0nm

Dominant Wavelength: 583.6nm

Color Purity: 0.493

Central Wave: 594.4nm

Gravity Wave: 597.3nm

CRI: $R_a=83.2$ TM30: $R_f=84$, $R_g=95$ GAI: $GAI_BB_8=97.7$, $GAI_BB_15=105.7$, $GAI_EES=56.4$


R1 =83	R2 =94	R3 =94	R4 =80	R5 =84	R6 =93	R7 =80	R8 =59
--------	--------	--------	--------	--------	--------	--------	--------

R9 =10	R10=85	R11=80	R12=74	R13=86	R14=98	R15=75	
--------	--------	--------	--------	--------	--------	--------	--

Color Quality Scale: $Q_a=82.7$, $Q_f=84.1$, $Q_p=84.3$, $Q_g=91.5$

Q1 =79	Q2 =94	Q3 =84	Q4 =79	Q5 =82	Q6 =84	Q7 =84	Q8 =86
--------	--------	--------	--------	--------	--------	--------	--------

Q9 =95	Q10=91	Q11=86	Q12=83	Q13=82	Q14=73	Q15=75	
--------	--------	--------	--------	--------	--------	--------	--



Photometric Parameters

Luminous Flux: 1574.3 lm

Efficiency: 128.09 lm/W

Radiant Power: 4.802 W

Total mains efficacy: 128.09 lm/W Energy Efficiency Class: E (EU 2019/2015)

Electric Parameters

Voltage: 229.40V

Current: 0.1050A

Power: 12.29W

Power Factor: 0.5110

Frequency: 49.99Hz

Test Information

Scan Range: 380~800:1nm

Stabilization Time: 0 Sec ALC.: 1.0000

Max of Signal: 44233 (4171)

Photometric Method: sphere-spectroradiometer

Photometric Condition: Sphere diameter: 1.50m, 4 π

CCD Integration Time: 359.99 ms

Condition: Tx:29.4°C, Ti:28.0°C, R.H.:60%

Test Lab:


Operator:

Test Device: CMS-2S (Plus)

Test Time: 2022-09-29 10:47:51

Inspector:

Model placed on the Union market from 05/01/2023



EPREL registration number: 1653545

<https://eprel.ec.europa.eu/qr/1653545>

Supplier: Globo Handels GmbH (Importer)

Website:

Customer care service:

Name: GLOBO Handels GmbH

Website:

Email: office@globo-lighting.com

Phone: +43425332050

Address:

Gewerbestraße 3
9184 St. Peter
Austria