

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LOOM Design

Supplier's address: Main Office, Lilleringvej 30, 8462 Aarhus Harlev, DK

Model identifier: 854-002

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	LED		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

Parameter	Value	Parameter	Value
-----------	-------	-----------	-------

General product parameters:

Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	12	Energy efficiency class	G
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	314 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode power (P_{on}), expressed in W	11,4	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer dimensions without separate control gear, light-	Height	78	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	1	
	Depth	120	
			See image in last page

ing control parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,462 0,415
Parameters for LED and OLED light sources:			
R9 colour rendering index value	58	Survival factor	0,99
the lumen maintenance factor	0,96		

(a) : not applicable;

(b) : not applicable;



Lightsource Test Report

Product Infomation


Product Type: 854-001
Product Number: 21

Product Spec: 854-001

CIE Colorimetric Parameters

Chromaticity coordinates: $x=0.4617$ $y=0.4148$ $u(u')=0.2618$ $v=0.3528$ $v'=0.5292$
 CCT: $T_c=2707K$ ($duv=0.00140$) Color Ratio: $R=0.261$ $G=0.719$ $B=0.019$
 Peak Wavelength: 625.4nm Half Bandwidth: 150.6nm
 Dominant Wavelength: 583.7nm Color Purity: 0.631
 CRI: $R_a=91.0$, $avgR(1\sim14)=87.7$, $avgR(1\sim15)=87.7$ TM30: $R_f=90$, $R_g=101$
 GAI: $GAI_{BB_8}=95.2$, $GAI_{BB_15}=99.7$, $GAI_{EES}=46.5$

R1 =91	R2 =93	R3 =94	R4 =93	R5 =91	R6 =92	R7 =93	R8 =82
R9 =57	R10=83	R11=93	R12=78	R13=92	R14=96	R15=87	
Color Quality Scale: $Q_a=89.2$, $Q_f=91.2$, $Q_p=91.8$, $Q_g=96.1$							
Q1 =86	Q2 =96	Q3 =87	Q4 =88	Q5 =89	Q6 =87	Q7 =88	Q8 =92
Q9 =96	Q10=92	Q11=92	Q12=92	Q13=92	Q14=86	Q15=86	



Photometric Parameters

Luminous Flux: 314.09 lm
EEI: 0.37
Pupil Flux: 369.14 Plm

Efficiency: 27.19 lm/W
Energy Efficiency Class: B (EU 874-2012)
Pupil Lumens Per Watt: 31.96 Plm/W

Radiant Power: 1.075 W
Pupil Factor (Kp): 1.175

Electric Parameters

Voltage: 220.60V
Power Factor: 0.9960

Current: 0.0530A
Frequency: 49.99Hz

Power: 11.55W

Test Infomation


Scan Range: 380~800:1nm
Stabilization Time: 1 Min ALC.: 1.0000
Max of Signal: 31637 (2228)

Photometric Method: sphere-spectroradiometer
Photometric Condition: Sphere diameter: 1.50m, 4π
CCD Integration Time: 1000.00 ms

Condition: $T_x:17.9^{\circ}C$, $T_i:14.9^{\circ}C$, R.H.:60%
Test Lab:
Operator: CHEN

Test Device: Inventfine CMS-2S (Plus)
Test Time: 2024-01-23 17:21:23
Inspector:

Model placed on the Union market from 01/07/2024



EPREL registration number: 2069751

<https://eprel.ec.europa.eu/qr/2069751>

Supplier: Lampefeber A/S (Importer)

Website: www.lampefeber.com

Customer care service:

Name: Main Office

Website: www.loom-design.com

Email: mail@lampefeber.com

Phone: +4586361722

Address:

Lilleringvej 30
8462 Harlev
Denmark