

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: GLOBO Handels GmbH

Supplier's address: GLOBO Handels GmbH, Gewerbestraße 3, 9184 St. Peter, AT

Model identifier: 16024-3

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	LED		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	18	Energy efficiency class	E
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	2 200 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power (P_{on}), expressed in W	16,5	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,50
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	83
Outer dimensions without separate control gear, lighting control	Height	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width		
	Depth		

parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,374 0,372	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	9	Survival factor	0,90	
the lumen maintenance factor	0,95			

(a) : not applicable;

(b) : not applicable;


Spectral test report for lamp

Product type : 16024-3-4000K Light source
Product No. :
Manufacturer : TAVIC

Test time : 2024/7/27 16:34:40
Test equipment : SPEC-3000A Spectrometer
Operator : 林溢

CIE Color Parameter

Chromaticity coordinates: $x=0.3683$ $y=0.3720$ $u=0.2190$ $v=0.3318$ $u^*=0.2190$ $v^*=0.4977$
Color temperature: 4315 K ($duv=+0.00152$) Color difference: SDCM(IEC/F4000)=5.5 Main Wavelength: 484.3 nm Purity: 0.199
Peak wavelength: $\lambda_p=449.5$ FWHM: $\Delta\lambda_p=22.4$ nm Color ratio: R=0.186 G=0.780 B=0.034
Color rendering index: Ra=81.75 Color Fidelity: Rf=83.28 Color Gamut Rg=94.8 GAI=90.42
R1=79.7 R2=87.4 R3=93.5 R4=81.3 R5=80.0 R6=82.5 R7=86.1 R8=63.6
R9=1.6 R10=70.3 R11=80.2 R12=59.5 R13=82.2 R14=96.5 R15=73.4



Optical Parameter

Luminous flux: 2219.78 lm
Energy efficiency index (EEI): 126.196
MOVE=2171.444 MES1=1919.626

luminous efficiency: 126.2 lm/w Radiant flux: 6.703 W
Energy efficiency class: E (EU 2019/2015) (EU 874)

Electrical Parameter

Voltage(V): 230.26 Current(A): 0.0807 Watte(W): 17.590 Power factor: 0.9458

Test Information


Temperature : Deg C
Test range : 350-800nm : 1nm
Preheat time : 0(min)

Humidity :
Peak AD. : 49931 (76.2%)
Integral time. : 1163.01 (ms)

MEASUREFINE

Hangzhou Huipu Instrument Co., Ltd. <http://www.measurefine.com>

Model placed on the Union market from 01/08/2024



EPREL registration number: 2120511

<https://eprel.ec.europa.eu/qr/2120511>

Supplier: Globo Handels GmbH (Importer)

Website:

Customer care service:

Name: GLOBO Handels GmbH

Website:

Email: office@globo-lighting.com

Phone: +43425332050

Address:

Gewerbestraße 3
9184 St. Peter
Austria