

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LIGHT-POINT

Supplier's address: Legal, Grønnegade 3, 2. tv 1107 København K Danmark

Model identifier: 290110 - LINEA W3

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	LED		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	Yes	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes

Product parameters

Parameter		Value	Parameter	Value
General product parameters:				
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer		36	Energy efficiency class	F
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		3 330 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2700...3000
On-mode power (P_{on}), expressed in W		35,7	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer dimensions without separate control gear, lighting control	Height	65	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width	70		
	Depth	600		

parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,425 0,398	
Parameters for directional light sources:				
Peak luminous intensity (cd)	203	Beam angle in degrees, or the range of beam angles that can be set	115	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	47	Survival factor	0,90	
the lumen maintenance factor	0,70			

(a) : not applicable;

(b) : not applicable;

Light Source Test Report



Color Parameters:

Chromaticity Coordinate: $x=0.4257$ $y=0.3985$

Chromaticity Coordinate: $u'=0.2457$ $v'=0.5175$ ($duv=-5.90e-04$)

$T_c=3152K$ Dominant WL: $L_d=582.4nm$ Purity=47.4% Centroid WL: $594.0nm$

Ratio: $R=24.4\%$ $G=73.1\%$ $B=2.4\%$ Peak WL: $L_p=615.0nm$ HWL: $166.1nm$

Render Index: $R_a=89.2$

$R1=89$ $R2=92$ $R3=95$ $R4=90$ $R5=89$ $R6=90$ $R7=90$

$R8=78$ $R9=47$ $R10=82$ $R11=91$ $R12=81$ $R13=89$ $R14=97$ $R15=85$

Photo Parameters:

Flux: $2634.8 lm$ $Fe: 8.8888 W$ Efficacy: $92.84 lm/W$

Electrical Parameters:

Lamp : $U=221.3V$ $I=0.1318A$ $P=28.38W$ $PF=0.9732$

Instrument Status:

Scan Range: $380.0nm-800.0nm$ Interval: $5.0nm[0]$

REF=12146 ($R=2$)

$\%=-0.050\%$

$I_p=45090$ ($G=4, D=54$)

PMT: 29.3 centigrade [150.0]

Product Type: 640089-112-60 (砂白裸光源)

Number: 206

Temperature: $25.3 deg$

Test Operator: Eric

Software: V2.00.128

Test Department: LCZ

Humidity: 65.0%

Test Date: 2025-09-05 11:45:46

Instrument: PMS-80_V1 (SN: G107113CJ6321129)

Model placed on the Union market from 10/09/2025.



EPREL registration number: 2467775

<https://eprel.ec.europa.eu/qr/2467775>

Voluntary parameters:

GTIN identifier: 5711389901103

Supplier: LIGHT-POINT A/S (Manufacturer)

Website:

Customer care service:

Name: Legal

Website:

Email: bkr@light-point.com

Phone: +4522896666

Address:

Grønnegade 3, 2. tv
1107 København K
Danmark