

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LOOM Design

Supplier's address: Main Office, Lilleringvej 30, 8462 Aarhus Harlev, DK

Model identifier: 880-006

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	LED		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters


Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	15	Energy efficiency class	G
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	627 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode power (P_{on}), expressed in W	15,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer dimensions without separate control gear, light-	Height	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width		
	Depth		

ing control parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,458 0,410	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	63	Survival factor	1,00	
the lumen maintenance factor	0,96			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ_1)	0,85	Colour consistency in McAdam ellipses	3	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0	

(a) '-': not applicable;

(b) '-': not applicable;

Spectrum Test Report



Color Parameters:

Chromaticity Coordinate: $x=0.4594$ $y=0.4086$ $u'=0.2631$ $v'=0.5265$
CCT=2691K (Duv=-0.0007) Dominant WL:Ld =584.5nm Purity=60.6%
Ratio:R=26.9% G=70.4% B=2.6% Peak WL:Lp=622.7nm FWHM=139.1nm
Render Index:Ra=94.4 TM30:Rf=92 Rg=99
R1 =96 R2 =99 R3 =98 R4 =96 R5 =96 R6 =97 R7 =91
R8 =83 R9 =63 R10=97 R11=98 R12=88 R13=97 R14=100 R15=91

Photo Parameters:

Flux = 626.6 lm Eff. : 41.77 lm/W Fe = 2.223 W

Electrical parameters:

V = 219.50 V I = 0.1437 A P = 15.00 W PF = 0.4757

Status: Integral T = 830 ms Ip = 52149 (80%)

Model:WWV350B 藏蓝色
Tester:彭金英
Temperature:25.3Deg
Manufacturer:SAT

Number:WWV350B 藏蓝色
Date:2025-09-15 11:21:41
Humidity:51%
Remarks:系数1.17

EPREL registration number: 2573959

Model placed on the Union market from 12/12/2025.



<https://eprel.ec.europa.eu/qr/2573959>

Supplier: Lampefeber A/S (Importer)

Website: www.lampefeber.com

Customer care service:

Name: Main Office

Website: www.loom-design.com

Email: mail@lampefeber.com

Phone: +4586361722

Address:

Lilleringvej 30
8462 Harlev
Denmark