

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** OSRAM

**Supplier's address:** LEDVANCE GmbH, Parkring 33, Garching, Germany

**Model identifier:** AC34294

## Type of light source:

|   |       |                                 |      |
|---|-------|---------------------------------|------|
| Lighting technology used:                           | CFLni | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | 2G11  |                                 |      |
| Mains or non-mains:                                 | NMLS  | Connected light source (CLS):   | No   |
| Colour-tuneable light source:                       | No    | Envelope:                       | -    |
| High luminance light source:                        | No    |                                 |      |
| Anti-glare shield:                                  | No    | Dimmable:                       | Yes  |


## Product parameters

| Parameter  | Value                  | Parameter  | Value   |
|--|------------------------|--|---|
| <b>General product parameters:</b>   |                        |  |   |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer  | 58                     | Energy efficiency class  | G   |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 3 600 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000   |
| On-mode power ( $P_{on}$ ), expressed in W   | 55,0                   | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal   | 0,00  |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal  | -                      | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 90  |
| Outer dimensions without separate control gear, lighting control   | Height                 | 538  | Spectral power distribution in the range 250 nm to 800 nm, at full-load |
|  | Width                  | 17   |   |
|  | Depth                  | 17   |   |
|  |                        |  | See image in last page  |


|   |   |                                    |                |
|---|---|------------------------------------|----------------|
| parts and non-lighting control parts, if any (millimetre) |   |                                    |                |
| Claim of equivalent power <sup>(a)</sup>                  | - | If yes, equivalent power (W)       | -              |
|   |   | Chromaticity coordinates (x and y) | 0,440<br>0,403 |

(a): not applicable;

(b): not applicable;



Model placed on the Union market from 12/10/2021



**EPREL registration number:** 546520

<https://eprel.ec.europa.eu/qr/546520>

**Supplier:** LEDVANCE GmbH (Manufacturer)

**Website:** <http://www.ledvance.com/>

**Customer care service:**

**Name:** LEDVANCE GmbH

**Website:**

**Email:** [contact@ledvance.com](mailto:contact@ledvance.com)

**Phone:** +49 89-780673-100

**Address:**

Parkring 33, Garching, Germany