

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: G&L Handels GmbH

Supplier's address: G&L Handels GmbH, Gerhard-Ellrodt-Straße 52, 04249 Leipzig, DE

Model identifier: 957013102

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	N/A		
Mains or non-mains:	MLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	Yes		
Anti-glare shield:	No	Dimmable:	No



Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	13	Energy efficiency class	C
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	2 442 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power (P_{on}), expressed in W	13,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,39
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	0,39	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	81
Outer dimensions without separate control gear, lighting control	Height	770	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	67	
	Depth	27	
			See image in last page

parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,380 0,380
Parameters for LED and OLED light sources:			
R9 colour rendering index value	1	Survival factor	0,90
the lumen maintenance factor	0,96		
Parameters for LED and OLED mains light sources:			
displacement factor (cos ϕ_1)	0,50	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	Yes ^(b)	If yes then replacement claim (W)	1
Flicker metric (Pst LM)	0,9	Stroboscopic effect metric (SVM)	0,9

(a)¹ : not applicable;

(b)¹ : not applicable;



Model placed on the Union market from 01/01/2020



EPREL registration number: 857625

<https://eprel.ec.europa.eu/qr/857625>

Supplier: G & L Handels GmbH (Manufacturer)

Website: www.gl-handels.de

Customer care service:

Name: G&L Handels GmbH

Website:

Email: info@gl-handels.de

Phone: 0341 4422 7922

Address:

Gerhard-Ellrodt-Straße 52

04249 Leipzig

Germany