

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** G&L Handels GmbH

**Supplier's address:** G&L Handels GmbH, Gerhard-Ellrodt-Straße 52, 04249 Leipzig, DE

**Model identifier:** 957016102

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	N/A		
Mains or non-mains:	MLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	Yes		
Anti-glare shield:	No	Dimmable:	No



## Product parameters

Parameter	Value	Parameter	Value
<b>General product parameters:</b>			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	16	Energy efficiency class	C
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	3 000 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power ( $P_{on}$ ), expressed in W	16,0	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0,48
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	0,48	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	81
Outer dimensions without separate control gear, lighting control	Height	908	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	67	
	Depth	27	
			See image in last page


parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,380 0,380
<b>Parameters for LED and OLED light sources:</b>			
R9 colour rendering index value	1	Survival factor	0,90
the lumen maintenance factor	0,96		
<b>Parameters for LED and OLED mains light sources:</b>			
displacement factor (cos $\phi_1$ )	0,70	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	Yes <sup>(b)</sup>	If yes then replacement claim (W)	1
Flicker metric (Pst LM)	0,9	Stroboscopic effect metric (SVM)	0,9

(a)<sup>1</sup> : not applicable;

(b)<sup>1</sup> : not applicable;



Model placed on the Union market from 01/01/2020



**EPREL registration number:** 857626

<https://eprel.ec.europa.eu/qr/857626>

**Supplier:** G & L Handels GmbH (Manufacturer)

**Website:** [www.gl-handels.de](http://www.gl-handels.de)

**Customer care service:**

**Name:** G&L Handels GmbH

**Website:**

**Email:** [info@gl-handels.de](mailto:info@gl-handels.de)

**Phone:** 0341 4422 7922

**Address:**

Gerhard-Ellrodt-Straße 52

04249 Leipzig

Germany