
## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources						
Supplier's name or trade mark: Scandinavian Lighting Concept						
Supplier's address: The Light Group, Sagmyra 2a, 4624 Kristiansand, NO						
Model identifier: SLC1246						
Type of light source:						
Lighting techno	logy used:	LED	Non-directional or directional:	DLS		
Light source cap-type		N/A				
(or other electri	c interface)					
Mains or non-mains:		NMLS	Connected light source (CLS):	No		
Colour-tuneable	e light source:	No	Envelope:	-		
High luminance		No				
Anti-glare shield:		No	Dimmable:	Yes		
Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		17	Energy efficiency class	F		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		753 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 127		
On-mode power (P <sub>on</sub> ), expressed in W		7,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	97		
Outer dimen-	Height	16	Spectral power dis-	See image		
sions without separate con- trol gear, light- ing control	Width Depth	16 2	tribution in the range 250 nm to 800 nm, at full-load	in last page		

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,433			
		nates (x and y)	0,403			
Parameters for directional light sources:						
Peak luminous intensity (cd)	240	Beam angle in degrees, or the range of beam angles that can be set	117			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	87	Survival factor	0,96			
the lumen maintenance factor	1,00					

(a)'-': not applicable; (b)'-': not applicable;



Model placed on the Union market from 01/08/2021



EPREL registration number: 863209 https://eprel.ec.europa.eu/qr/863209

Supplier: THE LIGHT GROUP AS (Manufacturer) Website: www.tlg.no

**Customer care service:** 

Name: The Light Group Website: www.tlg.no

Email: post@tlg.no Phone: +4738002101

Address: Sagmyra 2a 4624 Kristiansand

Norway