

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** Scandinavian Lighting Concept

**Supplier's address:** The Light Group, Sagmyra 2a, 4624 Kristiansand, NO

**Model identifier:** SLC1102

**Type of light source:**

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	N/A		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes

## Product parameters


Parameter	Value	Parameter	Value
<b>General product parameters:</b>			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	9	Energy efficiency class	E
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	753 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 127
On-mode power ( $P_{on}$ ), expressed in W	7,0	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0,00
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	97
Outer dimensions without separate control gear, lighting control	Height	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width		
	Depth		

parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,433 0,403	
<b>Parameters for directional light sources:</b>				
Peak luminous intensity (cd)	255	Beam angle in degrees, or the range of beam angles that can be set	117	
<b>Parameters for LED and OLED light sources:</b>				
R9 colour rendering index value	87	Survival factor	0,96	
the lumen maintenance factor	1,00			

(a) : not applicable;

(b) : not applicable;

## Spectrum



## Colorimetric Parameters

Chromaticity Coordinate:  $x = 0.4314$   $y = 0.4083$  /  $u' = 0.2452$   $v' = 0.5222$  ( $duv=2.50e-03$ )

CCT= 3130K Prcp WL:  $L_d=581.4nm$  Purity=52.0%

Peak WL:  $L_p=631nm$  FWHM:  $=178.6nm$  Ratio:R=23.9% G=72.9% B=3.2%


Render Index:  $R_a = 97.2$  TM30:  $R_f=95$   $R_g=99$

R1 =98 R2 =98 R3 =96 R4 =98 R5 =97 R6 =97 R7 =98

R8 =95 R9 =87 R10=94 R11=99 R12=81 R13=98 R14=97 R15=96

CQS Parameters:  $Q_a = 96.3$

Model placed on the Union market from 01/08/2021



**EPREL registration number:** 875107

<https://eprel.ec.europa.eu/qr/875107>

**Supplier:** THE LIGHT GROUP AS (Manufacturer)

**Website:** [www.tlg.no](http://www.tlg.no)

**Customer care service:**

**Name:** The Light Group

**Website:** [www.tlg.no](http://www.tlg.no)

**Email:** [post@tlg.no](mailto:post@tlg.no)

**Phone:** +4738002101

**Address:**

Sagmyra 2a  
4624 Kristiansand  
Norway