
Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources						
Supplier's name or trade mark: Scandinavian Lighting Concept						
Supplier's address: The Light Group, Sagmyra 2a, 4624 Kristiansand, NO						
Model identifier: SLC1236						
Type of light source:						
Lighting technology used:		LED	Non-directional or directional:	DLS		
Light source cap-type		N/A				
(or other electric interface)						
Mains or non-mains:		NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:		No	Envelope:	-		
High luminance light source:		No				
Anti-glare shield:		No	Dimmable:	Yes		
Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		9	Energy efficiency class	F		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		696 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode power (P _{on}), expressed in W		7,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	97		
Outer dimen-	Height	16	Spectral power dis-	See image		
sions without	Width	16	tribution in the	in last page		
separate con- trol gear, light- ing control	Depth	2	range 250 nm to 800 nm, at full-load			

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,433			
		nates (x and y)	0,403			
Parameters for directional light sources:						
Peak luminous intensity (cd)	240	Beam angle in degrees, or the range of beam angles that can be set	116			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	88	Survival factor	0,96			
the lumen maintenance factor	1,00					

(a)'-': not applicable; (b)'-': not applicable;



Model placed on the Union market from 01/08/2021



EPREL registration number: 875119 https://eprel.ec.europa.eu/qr/875119

Supplier: THE LIGHT GROUP AS (Manufacturer) Website: www.tlg.no

Customer care service:

Name: The Light Group Website: www.tlg.no

Email: post@tlg.no Phone: +4738002101

Address: Sagmyra 2a 4624 Kristiansand

Norway