

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** Vibia

**Supplier's address:** Vibia Lighting, progres 4-6, 08850 Gava gava Barcelona, ES

**Model identifier:** 592610/1A

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	Renovable PCB		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes

## Product parameters

Parameter	Value	Parameter	Value
<b>General product parameters:</b>			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	50	Energy efficiency class	E
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	6 598 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode power ( $P_{on}$ ), expressed in W	50,0	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0,10
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer dimensions without separate control gear, lighting control	Height	900	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	200	
	Depth	360	
			See image in last page

parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,459 0,408	
<b>Parameters for LED and OLED light sources:</b>				
R9 colour rendering index value	56	Survival factor	-	
the lumen maintenance factor	-			

(a) : not applicable;

(b) : not applicable;

$\lambda_p$   
nm

624


$\lambda_p V$   
mW/m<sup>2</sup>

11.75

11.75



Model placed on the Union market from 01/01/2010



**EPREL registration number:** 905092

<https://eprel.ec.europa.eu/qr/905092>

**Supplier:** Vibia Ligting, SLU (Manufacturer)

**Website:** [www.vibia.com](http://www.vibia.com)

**Customer care service:**

**Name:** Vibia Lighting

**Website:** [www.vibia.com](http://www.vibia.com)

**Email:** [vibia@vibialighting.com](mailto:vibia@vibialighting.com)

**Phone:** +34 934 796 970

**Address:**

progres 4-6  
08850 gava  
Spain