

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: ANTIDARK

Supplier's address: Antidark Aps, damgårdvej 2, 5500 Middelfart , DK

Model identifier: 2-215-25-1

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	LED		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	Yes	Dimmable:	Yes


Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	12	Energy efficiency class	G
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	795 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	1800...2700
On-mode power (P_{on}), expressed in W	11,9	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer dimensions without separate control gear, lighting control	Height	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width		
	Depth		

parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,457 0,408	
Parameters for directional light sources:				
Peak luminous intensity (cd)	1 877	Beam angle in degrees, or the range of beam angles that can be set	113	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	68	Survival factor	1,00	
the lumen maintenance factor	0,96			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ_1)	1,00	Colour consistency in McAdam ellipses	3	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4	

(a) '-': not applicable;

(b) '-': not applicable;



Color Parameters:

Chromaticity Coordinate: $x=0.4579$ $y=0.4082$ $u'=0.2623$ $v'=0.5261$

$T_c=2709K$ ($Duv=-0.0007$) Dominant WL: $L_d=584.4nm$ Purity=60.0%

Red Ratio: $R=28.1\%$ Peak WL: $L_p=631.2nm$ HWL: $L_{hd}=155.2nm$

Render Index: $R_a=92.5$

$R1=94$ $R2=94$ $R3=91$ $R4=93$ $R5=92$ $R6=92$ $R7=95$

$R8=88$ $R9=71$ $R10=84$ $R11=93$ $R12=75$ $R13=94$ $R14=94$ $R15=92$

Photo Parameters:

Flux = 657.9 lm Eff. : 55.48 lm/W $F_e = 2.426 W$

Electrical parameters:

$V = 33.84 V$ $I = 0.3504 A$ $P = 11.86 W$ PF = 1.000


LEVEL:OUT WHITE:ANSI_2700K

Status: Integral $T = 53 ms$ $I_p = 46746 (71\%)$

Model:
Tester:Ricon
Temperature:25.3Deg
Manufactory:ANTIDARK

Number:2-215-25-2
Date:2021-11-10
Humidity:65.0%
Remarks:

Model placed on the Union market from 08/07/2019



EPREL registration number: 930085

<https://eprel.ec.europa.eu/qr/930085>

Supplier: Antidark Aps (Importer)

Website: www.antidark.dk

Customer care service:

Name: Antidark Aps

Website:

Email: tj@scanstudio.dk

Phone: +4540187474

Address:

damgårdvej 2
5500 Middelfart
Denmark