

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Hera GmbH & Co KG

Supplier's address: FE, Dieselstraße 9, 32130 Enger Herford, DE

Model identifier: Dynamic LED Top-Stick F

Type of light source:

| | | | |
|-----------------------------------------------------|------|---------------------------------|----------------------------|
| Lighting technology used: | LED | Non-directional or directional: | DLS |
| Light source cap-type (or other electric interface) | nein | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | Only with specific dimmers |

Product parameters

| Parameter | Value | Parameter | Value |
|-----------|-------|-----------|-------|
|-----------|-------|-----------|-------|


General product parameters:

| | | | |
|------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------|
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer | 21 | Energy efficiency class | G |
| Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 1 000 in Wide cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2700...5000 |
| On-mode power (P_{on}), expressed in W | 19,2 | Standby power (P_{sb}), expressed in W and rounded to the second decimal | 0,00 |
| Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 82 |
| Outer dimensions without separate control gear, light- | Height | 1 200 | Spectral power distribution in the range 250 nm to 800 nm, at full-load |
| | Width | 40 | |
| | Depth | 12 | |
| | | | See image in last page |


| | | | |
|-----------------------------------------------------------------------|------|--------------------------------------------------------------------|----------------|
| ing control parts and non-lighting control parts, if any (millimetre) | | | |
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - |
| | | Chromaticity coordinates (x and y) | 0,349 0,359 |
| Parameters for directional light sources: | | | |
| Peak luminous intensity (cd) | 1 | Beam angle in degrees, or the range of beam angles that can be set | 100 |
| Parameters for LED and OLED light sources: | | | |
| R9 colour rendering index value | 0 | Survival factor | 0,00 |
| the lumen maintenance factor | 0,00 | | |

(a)¹⁾ : not applicable;

(b)¹⁾ : not applicable;



Model placed on the Union market from 08/06/2021



EPREL registration number: 949676

<https://eprel.ec.europa.eu/qr/949676>

Supplier: Hera GmbH & Co KG (Manufacturer)

Website: www.hera-online.de

Customer care service:

Name: FE

Website: www.hera-online.de

Email: rohs@hera-online.de

Phone: 05224911309

Address:

Dieselstraße 9

32130 Enger

Germany